

# Monustop®

## How to order

Monustop® is available in 290 ml cartridges packed per 12 in a box. To order your specific Monustop®, please find below the article and EAN codes:

Colour:	Article code:	EAN code:
White	10870400	8711595090278
Grey	11715700	8711595122603
RAL 6005 (Moss green)	11814000	8711595149983

## General information

A joint with the correct dimensions is able to absorb movements between building materials. The joint depth should always be in the correct relationship of the joint width. A general rule is the ratio of joint depth to the width of the joint with a joint width till 10 mm is 1:1, with a minimum of 5 mm in width and depth. For joints wider than 10 mm, the depth is the width divided by 3 plus 6mm. For more information see the Technical Bulletin Joint Dimensions in the Knowledge Base on our website.

## Limitations

Not suitable for PE, PP, PC, PMMA, PTFE, neoprene and bituminous substrates. Not suitable for continuous water load. Not suitable in combination with chlorides (pools).



## Centre of Excellence

### Better results through Knowledge

Den Braven 's company payoff is "Better results through Knowledge". Our Centre of Excellence accumulates knowledge which provides her with the latest market insights, developments and trends. This knowledge is shared within the Den Braven Group and amongst our customers and end-users.

This process enables our relations to achieve higher efficiency and better results. This is the true meaning of "Better results through Knowledge". Visit our website to discover more about what the Centre of Excellence could mean for you!

[denbraven.com](http://denbraven.com)



## Den Braven



## Monustop

Fast curing alternative for putty based on hybrid technology

BETTER RESULTS THROUGH KNOWLEDGE

# Monustop®

Fast curing alternative  
for putty based on hybrid  
technology



- Excellent tooling properties in combination with Finisher and joint spatula
- Fast curing
- Excellent and fast paintable with water based and synthetic paints
- Adheres perfectly without primer on most, even damp, surfaces
- Durable permanent elastic
- No shrinkage and bubble free
- High mechanical resistance
- Free of isocyanates, solvents and silicones



## Monustop®

### Product Descriptions

Monustop® is a fast curing alternative for putty, based on hybrid technology which cures under influence of humidity to form a durable elastic rubber.

### Applications

Monustop® has been especially developed for durable elastic sealing of single, insulation and monumental glass\* in wood, metal and concrete frames without glazing beads.



## Monustop®

### Technical Performances

Density	1,16 g/ml
Shore-A hardness	27°
Elongation at break	275%
Tensile strength	0,85 Mpa
100% Modulus	0,50 Mpa
Skin formation	20 minutes

Visit our website to download the full technical specifications of the Monustop®.

\* Compatibility with sealed edges of insulation glass cannot be with sealed edges of insulation glass cannot be guaranteed, as the compositions on sealant for the edges of insulating glass can be different or changed by the producer of insulated glass. Advices concerning the compatibility of glazing sealants to the sealed edge of double glazing are based on experience and therefore not guaranteed.



### Visit Den Braven YouTube channel

Den Braven offers a wide variety of USP, Application and Commercial movies via here website and YouTube channel. Scan the below displayed QR Code to visit the USP movie of the original Monustop®.



BETTER RESULTS THROUGH KNOWLEDGE

denbraven.com